



CURRENT: IF=20*6=120mA, 3.2V(REF.)

Pin Assignment	
1	GND
2	RESET
3	CS
4	SCLK
5	IC-DI(INC)
6	SDI
7	SDO
8	DB0
9	DB1
10	DB2
11	DB3
12	DB4
13	DB5
14	DB6
15	DB7
16	DB8
17	DB9
18	DB10
19	DB11
20	DB12
21	DB13
22	DB14
23	DB15
24	DB16
25	DB17
26	GND
27	VS
28	HS
29	DOTCLK
30	ENABLE
31	GND
32	IOVC
33	VCC
34	XR
35	YL
36	XL
37	YU
38	LED_A
39	LED_K
40	NC

LCD type	3.5" TFT, Transmissive, Normally black, TN
Resolution	320(RGB)*480
View direction	All of Clock
Driver IC	ILI9488
Color Depth	282K
Interface Types	RGB
Operating voltage	3.3V
TFT/Lens	With RTP
Backlight LEDs	6LEDs
Surface luminance	250mIn, 300typ(cd/m ²)
Operating temperature	-20 C ~ 70 C
Storage temperature	-30 C ~ 80 C
Storage Humidity	60%~90% max

Need to pay attention to

the key size with *



东莞市一众显示科技有限公司
DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.

版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
V1	Initial Release	Sep-10-2018	M M	Unnoted tolerance ±0.2			
V2							
V3							